DESCRIPTION APPROVED INFORMATION IN THIS DRAWING PROVIDED FOR REFERENCE ONLY **SCALE 1:3** 17.000±.020 [431.80±0.51] 5.313 6.375±.010 5.313 [134.94] [161.93±0.25] [134.94] Ø3.910 .06 x 45°±5° 3.25 99.31 1.6 82.6 GROOVE TYP TYP. TYPICAL BOTH ENDS TYP. $\emptyset 4.00$ [101.5] Ø2.13X 90°±10° INCL. .250 [54] Ø2.001^{+.000} 6.35 .375 TYP. 9.53 **GROOVE** TYP. NOTE(s), UNLESS OTHERWISE SPECIFIED. BELDEN PART NUMBER: DUJ-HD4000x2000 (1) UNIVERSAL JOINT IS MARKED W/ "BELDEN" LOGO, PART NUMBER / DRAWING NUMBER, REVISION LEVEL (IF ANY), DATE OF MANUFACTURE (MO/YR), AND BELDEN JOB NUMBER. (2) UNIVERSAL JOINT IS LUBRICATED w/ LUBRIPLATE 1200-2, NLGI GRADE 2, AW/EP, LITHIUM GREASE OR EQUIVALENT DO NOT SCALE DRAWING (3) UNIVERSAL JOINT IS CAPABLE OF OPERATING AT ANY ANGLE UP TO AND INCLUDING 45°, 90° FOR THE DOUBLE UNIVERSAL JOINT. INLESS OTHERWISE SPECIFIED Belden Universal STANDARD TOLERANCES, UNLESS OTHERWISE SPECIFIED ALLOY STEEL CHAMFER ALL HOLES BREAK ALL SHARP CORNEI AJH 11JUL18 (4) UNIVERSAL JOINT HAS STANDARD GROOVES TO ACCEPT INSTALLATION OF PROTECTIVE COVERS (BOOTS). RAWN DE-BURR ALL FEATURES HECKED BOOTS AVAILABLE SEPARATELY. REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALES. TURNED SURFACES: 63/ ANGULAR MACHINED: FRACTIONAL: TWO PLACE DECIMAL: THREE PLACE DECIMAL: FOUR PLACE DECIMAL: CONCENTRICITY: .(. ENG APPE ASSEMBLY, DOUBLE SEE DETAIL IFG APPI **UNIVERSAL JOINT** (5) REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALES FOR TORQUE CAPACITY. MILLED SURFACES: 125 C APPR. PROPRIETARY AND CONFIDENTIA COMMENTS (6) THIS DRAWING REPRESENTS A STANDARD BELDEN ITEM. SIZE DWG. NO. REV ALL HOLES TO BE LOCATED ON CENTERLINE (\$\mathbb{C}\) WITHIN .005* T.I.R CUSTOM UNIVERSAL JOINTS ARE AVAILABLE UPON REQUEST. PLEASE CONTACT BELDEN SALES. DUJ-HD4000x2000 NTERPRET GEOMETRIC TOLERANCES I.A.W. ASME Y14.5

FORM SW-A 5-18 8

SCALE: 3:5 WT (Lbs): 41.535 SHEET 1 OF 2